

LightStream[®] Full HD 1080p Projector

True-to-Life Color + Smart Design

PJD7720HD



Featuring true-to-life color and a smart design, the ViewSonic® LightStream® PJD7720HD 1080p projector delivers all you need for affordable, high-definition entertainment at home. Equipped with SuperColor™ technology and a high-brightness output, this projector strikes a perfect balance of color and light so that movies, games, and multimedia content are brought to life – even in rooms with high ambient light. And with stunning 1080p resolution, the PJD7720HD delivers perfect front of screen performance that can match the image quality of any Full HD monitor screen or laptop. A smart and intuitive design includes PortAll™—a hidden MHL/HDMI port perfect for wireless dongles (such as the optional ViewSonic WPG-300) that let you wirelessly stream multimedia content from a mobile device, or notebook PC, to the projector. So whether wirelessly streaming video or content from a tablet, or simply plugging in your entertainment center, the PJD7720HD is the ideal projector for vibrant multimedia and high-definition entertainment.

Key Features:

Full HD 1080p, 3200 Lumens Best-in-class color accuracy Enhanced 10W cube speaker Smart design


Designed for:

Home



LightStream[®] Full HD 1080p Projector

PJD7720HD



Focus Ring —
Zoom Ring —
Control Panel





Specifications

DISPLAY		
INPUT SIGNAL	Computer and Video	NTSC M(3.58MHz), 4.43MHz, PAL (B, D, G, H, I M, N, 60), SECAM (B. D. G. L. L1), SD 480i and 576i, ED 480p and 576p, HD 720p, 1080i, 1080p Fh: 15–100KHz, Fv: 24–120Hz
COMPATIBILITY	PC Mac®	Up to 1920x1080 Up to 1920x1080 (may require MAC adapter)
CONNECTOR	Digital Input Audio In Audio Out USB Control	HDMI 1.4 (x1) / HDMI/MHL (x1) 3.5mm mini jack (x2) 3.5mm mini jack (x1) Mini type B (mouse control and maintenance) RS232

AUDIO	Speaker	10W (x1)
NOISE LEVEL	Normal / Eco-mode	35 dB / 30 dB
POWER	Voltage Consumption	100~240VAC (Auto Switching), 50-60Hz (universal) 330W (max) / <0.5W (stand-by mode)
CONTROLS	Basic OSD	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source Display, Picture, Source, System Setup (Basic), System Setup (Advanced), Information (See user guide for full OSD functionality)
OPERATING CONDITIONS	Temperature Humidity Altitude	32–104° F (0–40° C) 10–90% (non-condensing) 0~6000 ft (1828.8m)
DIMENSIONS (W x H x D)	Physical Packaging	12.44 x 8.98 x 4.08 in. / 316 x 228 x 103.7 mm 16.14 x 8.86 x 17.72 in. / 410 x 225 x 450 mm
WEIGHT	Net Gross	
REGULATIONS		Mexico Energy test/Registration, EAC, TUV-S Mark (Argentina), India BIS, FCC, CE EMC, CB, CCC, RoHS, REACH, SVHC, WEE, ErP, Mexico NOM, cTUVus, RCM, PSB, KC
WARRANTY		1-year limited warranty on parts and labor, 90 day limited warranty on lamp

Optional Accessories (Sold Separately)

Wireless Presentation Gateway Dongle	WPG-300
3D Active Shutter Glasses	PGD-350
Universal Ceiling Mount	PJ-WMK-006
Carrying Case	PJ-CASE-009
Replacement Lamp	RLC-100
100" Matte White Screen	PJ-SCW-1001W
Cable Mangement Cover	PJ-CM-001

What's in the box?

PJD7720HD projector, power cable, remote control (batteries included), Quick Start Guide, ViewSonic Wizard CD (with User Guide)















